

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A composite anchor bolt comprising:  
a first anchor bolt configured to be installed projecting outside of a concrete frame;  
a second anchor bolt that is eccentrically positioned to the axis of the first anchor bolt; and  
a connecting part ~~for connecting~~that connects the first anchor bolt and the second anchor ~~bolt~~bolt, the first anchor bolt and the second anchor bolt being attached to the connecting part,  
~~wherein~~ the connecting part extends radially from the first anchor bolt to and past the second anchor bolt,  
the second anchor bolt being located in a radial center of the connecting part, thereby reducing the bending moment ~~which~~that is exerted locally on the connecting part ~~when due to a load is applied~~on the first anchor bolt.
2. (Currently Amended) A composite anchor bolt according to claim 1, wherein ~~the planar~~a planar configuration of the connecting part is made to be a polygonal or circular shape, thereby increasing the compressive force transfer area ~~of the projecting portion~~.
3. (Previously Presented) A composite anchor bolt according to claim 1, wherein the connecting part is formed to have top and bottom surfaces of a polygonal or circular shape, and the second anchor bolt is positioned at the center of the connecting part.
4. (Currently Amended) A composite anchor bolt according to claim 1, wherein the connecting part has an injection hole for ~~the adhesive~~an adhesive and an air hole.

5. (Currently Amended) A composite anchor bolt according to claim 1, wherein both of ~~the~~the first anchor bolt and the second anchor bolt ~~are formed with~~have the same ~~or different~~ diameters.

6. (Currently Amended) A composite anchor bolt according to claim 1, wherein the second anchor bolt has a larger diameter than the first anchor bolt, ~~and formed with a shorter length in the embedded concrete bolt.~~

7. (Currently Amended) A composite anchor bolt comprising:  
a first anchor bolt installed projecting outside of ~~the concrete~~a concrete frame;  
a second anchor bolt ~~which~~that is eccentrically positioned to the axis of the first anchor bolt; and

a connecting part for connecting the first anchor bolt and the second anchor ~~bolt~~bolt, the first anchor bolt and the second anchor bolt being attached to the connecting part,

wherein the center of the connecting part and the axis of the second anchor bolt are coaxial, and

a planar configuration of the connecting part is formed in a polygonal or circular shape, and the first anchor bolt is positioned toward a radial edge of the connecting part.

8. (Currently Amended) A composite anchor bolt according to claim 7, wherein the planar configuration of the connecting part is made either a circular, ~~triangular~~triangular, ~~quadrangular~~quadrangle, or ~~polygonal~~a polygonal configuration to increase ~~the adhesive~~an adhesive area of the composite anchor bolt with the concrete.

9. (Previously Presented) A composite anchor bolt according to claim 7, wherein a reinforcing portion is formed at a joining point between the second anchor bolt and the

connecting part to compensate for a bending moment which is exerted locally on the joining point.

10. (Currently Amended) A composite anchor bolt according to claim 7, wherein ~~of both~~both the first anchor bolt and the second anchor bolt ~~are formed with~~have the same ~~or different~~ diameters.

11. (Currently Amended) A composite anchor bolt according to claim 7, wherein the second anchor bolt has a ~~large~~larger diameter than that of the first anchor bolt, and ~~formed with a shorter length in the embedded concrete bolt.~~

12. (Currently Amended) A composite anchor bolt according to claim 7, wherein the connecting part has an injection hole for ~~the adhesive~~an adhesive and an air hole.

13. (Currently Amended) A composite anchor bolt according to claim 7, wherein at least one of the first anchor bolt and second anchor bolt is removably ~~attachable~~attached to the connecting part.

14. (Currently Amended) A composite anchor bolt comprising:  
a first anchor bolt installed projecting outside of ~~the concrete~~a concrete frame;  
a second anchor bolt ~~which~~that is eccentrically positioned to the axis of the first anchor bolt; and

a connecting part for connecting the first anchor bolt and the second anchor ~~bolt~~bolt, the first anchor bolt and the second anchor bolt being attached to the connecting part,

wherein the connecting part and second anchor bolt are formed together in a T-shape configuration, and the first anchor bolt is placed at ~~the end side~~an edge of the connecting part.

15. (Currently Amended) A composite anchor bolt according to claim 14, wherein at least one of the first anchor bolt and second anchor bolt is removably ~~attachable~~ attached to the connecting part.

16. (Currently Amended) A method of installing a composite anchor bolt comprising:

preparing a composite anchor bolt including a first anchor bolt and a second anchor bolt positioned eccentrically in a direction perpendicular to each other with a planar connecting part connecting the first and second anchor bolts,

the first anchor bolt projecting on the outside of a matrix in which the composite anchor bolt is embedded and ~~a second~~ the second anchor bolt being positioned eccentrically to the first anchor bolt relative to the planar connecting part projecting inside the matrix;

removing a cylindrical or polygonal core ~~from the~~ from a reinforcement covering margin to confirm ~~the position of the~~ a position of a reinforcement within the matrix, when the reinforcement is encountered in the anchor borehole position, the core corresponding to the shape of the connecting part, and surrounding the borehole;

drilling a borehole for the second anchor bolt; and

jointly attaching the composite anchor bolt,

wherein the planar connecting part extends radially from the first anchor bolt to and past the second anchor bolt.

17. (Currently Amended) The method of installing a composite anchor bolt according to claim 16, ~~wherein~~ wherein, after the second anchor bolt is set into the drilled borehole, ~~the adhesive~~ an adhesive is injected into an adhesive injection hole which is formed in the connecting part, air is released from an air hole which is formed in the connecting part, and the composite anchor bolt is attached.

18. (Previously Presented) The method of installing a composite anchor bolt according to claim 16, wherein a portion of the connecting part is projected outside from the concrete frame, and an equipment base is placed on the connecting part and attached with the first anchor bolt.

19. (New) A composite anchor bolt according to claim 1, wherein both the first anchor bolt and the second anchor bolt have different diameters.

20. (New) A composite anchor bolt according to claim 7, wherein both the first anchor bolt and the second anchor bolt have different diameters.